

DIGITAL CAMERA G-Shot P7533



Elegant & Stylish 7.0 Mega Pixel CCD Digital Camera

G-Shot P7533 is the latest generation of slide cover designs from Genius for lightweight digital cameras. It not only has similar features to the G-Shot P713, but also improves upon it with its unique specification.

G-Shot P7533 comes with the super **Sharp CCD** sensor, and the true **7.0 mega pixel resolution** enables you to shoot high quality images anytime and anywhere and you can get print your pictures from 2" x 3" to 12" x 18". With the 115K pixel 2.4" LTPS LCD panel, any image can be displayed with clear details in vivid color. The large monitor is helpful for you to capture subjects, review images and makes it easier to adjust each setting. Moreover, with the 650mAh rechargeable Lithium Ion battery; you can take up to **190 pictures** before it has to be recharged.

For more information about this impressive camera; just ask your sales person about the **G-Shot P7533**.



Selling Points

Multi-Scene Mode

You can select the scene mode according to the shooting scene. There are six available modes in the scene mode.

[A]	Auto	Select this mode to adjust point-and-shoot action.
[S]	Sport	Select this mode when you want to photograph fast-moving subjects.
[N]	Night	Select this mode when you want to capture people with an evening or night scene background.
[P]	Portrait	Select this mode when you want to capture an image that makes the person stand out against a defocused (blurred) background.
[L]	Landscape	Select this mode to capture an image with infinity focus, hard sharpness and high saturation.
[B]	Backlight	Select this mode when you want to capture images when the light comes from behind the object.

DIGITAL CAMERA G-Shot P7533



7.0 mega pixel Sharp CCD sensor

This camera delivers high quality and brilliant 3072 x 2304, 2560 x 1920, 1600 x 1200 and 640 x 480 resolution images.



2.4" LTPS LCD display – 115K pixels

Use the large LCD monitor to help you compose the best images and then examine them in detail.



4X Digital zoom

With the 4 times zoom, you are able to capture telephoto and wide-angle shots.



Slide Show

Enjoy photo playback automatically, it's very useful and entertaining feature for reviewing recorded images and ideal for presentations.



Thumbnail

It allows you to view nine thumbnail images on the LCD monitor at once so you can find your favorite image.



Direct Print function

Connect to any PictBridge™ compatible printer with the supplied USB cable and print directly from the camera. Images can be viewed and selected for printing right on the camera's LCD.

DIGITAL CAMERA G-Shot P7533

Genius
Live with Ideas



Supports up to 2GB SD card

You can use an additional SD card up to 2GB for memory expansion.

Friendly operation, easy to use!

Using Self-Timer



2sec. / 10 sec. / 10+2 sec.

Setting Flash

Off Forced Red-eye Reduction



Normal

Macro



Magnifying Images

4X Digital Zoom



Quick Setting Focus

Bundled Software



Ulead Photo Explorer

Ulead® Photo Explorer 8.0 lets you spend more time enjoying photos, music and videos and less time finding them. It's the all-in-one solution for owners of digital cameras, camcorders, scanners or anyone who wants to make it easier to keep track of their media

Ulead Photo Express



The Fast Track to Photo Fun

Ulead® Photo Express® 5 is home photo creativity software that makes it easy to edit and share digital photos and create fun photo projects. Edit and enhance images, browse your photo collection and express your creativity with stunning special effects and creative photo projects.

DIGITAL CAMERA G-Shot P7533



System requirements for USB Terminal

Recommended environment for USB terminal:

- Windows® environment
 - Pentium III 600 MHz processor or higher
 - Windows XP/2000/Vista
 - Minimum 128MB hard disk drive space
 - 64MB RAM
 - Available USB port
 - CD-ROM drive for software installation
- Mac environment
 - Mac OS 9.0 or later Minimum
 - Minimum 128MB hard disk drive space
 - 64MB RAM
 - Available USB port
 - CD-ROM drive for software installation

※ No Web Cam mode available for Mac and Vista.

Package Contents

- Digital Camera
- CD driver includes:
 - Ulead Photo Explorer
 - Ulead Photo Express(for Windows XP/Me/2000/98/98SE, Vista capable)
 - Web Cam Driver for Windows XP/Me/2000/98/98SE
 - Multi-Language User's Manual
- USB cable
- AC Power Adapter
- Battery Charger
- AC Plug Adapter for EU to US
- One Li-ion rechargeable battery
- Quick Guide
- Pouch
- Strap

Specifications

Item	Description
Image Sensor	7.0 Mega Pixels Sharp CCD Sensor
Image Resolution	Still image: 3072 x 2304, 2560 x 1920, 1600 x 1200, 640 x 480 Video clip: 320 x 240 / 24fps
Image Quality	Still image: Fine, Standard, Economy Movie image: Economy
Lens	Fixed Focus Lens, F No.: 3.2 Focal length: 7.1mm (equivalent to 42mm in 35mm camera)
Focus Range	Macro: 60 ~ 120 cm Normal: 120 ~ infinity
Digital Zoom	1X~4X for Preview, 1X~4X for Playback
Shutter Speed	1/1000 second, Mechanical Shutter
Flash	Auto, off, fill in, Red-eye reduction Flash Range: 0.6m~2.5m
LCD monitor	2.4" LTPS LCD High resolution 115K pixels display
Self-timer	2 sec, 10 sec, 10+2 second delay
Exposure compensation	Auto; Manual: +/-2.0EV in 0.3EV steps
White balance	Auto; Manual: Daylight, Cloudy, Tungsten, Fluorescent

DIGITAL CAMERA G-Shot P7533



ISO	Auto, 50, 100, 200, 400
Recording media	Internal: 16MB memory (14MB available for image storage). External: SD memory card (up to 2GB)
File format	EXIF 2.2 & DCF 1.0, DPOF 1.1, Motion-JPEG, JPEG
PictBridge	Yes
Interface	USB 2.0 full speed
Power supply	Li-ion rechargeable battery
UI OSD language	English, Russian, German, French, Italian, Spanish, Brazil Portuguese, Traditional Chinese
Giftbox language	English, Russian, German, French, Italian, Spanish, Brazil Portuguese, Czech, Turkish, Arabic, Traditional Chinese
Multi-Language User's Manual	English, Russian, German, French, Italian, Spanish, Brazil Portuguese, Turkish, Arabic, Traditional Chinese
Multi-Language Quick Guide	English, Russian, German, French, Italian, Spanish, Brazil Portuguese, Turkish, Arabic, Traditional Chinese
WEEE Information	
Body Weight (g)	Approx. 85g (without batteries and the SD memory card)
Body Dimension	Approx. 89.5 x 56 x 21.5 mm (without protruding parts)
Giftbox Dimension (L x W x H)	210 x 150 x 76 mm
Shipping Information	
PCs / Carton	10 pcs / Carton
N.W. / Carton	6.0 kgs
G.W. / Carton	7.0 kgs
CUFT:	1.3181 cuft/CTN
Dates available	
Sample available	July 31, 2007
Mass Production	July 31, 2007
Product number	32300067101 EAN: 4710268707547 UPC: 091163707547

DIGITAL CAMERA G-Shot P7533



Possible number of shots (still image)

The table shows the approximate shots that you can capture at each setting based on the capacity of the internal memory and the SD card. Built-in 16MB internal memory (14 MB available for image storage)

Image size	Quality	Internal Memory	SD Card Capacity						
			32MB	64MB	128MB	256MB	512MB	1GB	2GB
3072 x 2304	★★★	2	8	18	37	77	157	316	634
	★★	5	13	29	60	123	250	502	1006
	★	10	25	53	109	221	445	894	1792
2560 X 1920	★★★	4	11	24	51	104	210	422	846
	★★	7	18	39	81	165	334	670	1343
	★	13	32	68	141	286	576	1156	2317
1600 x 1200	★★★	10	23	49	101	205	413	830	1663
	★★	15	36	77	159	323	651	1307	2618
	★	26	62	131	270	547	1102	2211	4429
640 x 480	★★★	38	90	191	392	795	1601	3213	6437
	★★	53	124	262	538	1091	2198	4410	8835
	★	76	177	374	769	1557	3135	6291	12604

* The above data shows the standard testing results. The actual capacity varies according to the shooting conditions and settings.

Possible recording time (video clip)

The table below indicates the approximate duration of recording time depending on the capacity of the SD memory card.

Image size	Internal Memory	SD card capacity						
		32MB	64MB	128MB	256MB	512MB	1GB	2GB
320 x 240	00:00:26	00:00:57	00:01:56	00:03:56	00:07:55	00:15:52	00:31:48	01:03:39

* The values for the recording time may vary depending on the shooting conditions and settings.

Product Family

G-Shot D5123	G-Shot P6533	G-Shot P7545	G-Shot P732	G-Shot P8565
G-Shot DV601	G-Shot DV5122	G-Shot DV5133	G-Shot DV1210	G-Shot DV1112

Web Cam and Video Product Family

Slim 311R	Look 110	Eye 312	PF-A01	PF-801	MP-2101